

## Certificate of Product Approval

Certificate Number: 1137a

Issue: 03

### Armourpost Limited

Unit 14 Saltmeadows Road  
East Gateshead Industrial Estate  
Gateshead  
Tyne and Wear  
NE8 3AH

is authorised to use the LPCB mark in association with the product(s) listed in this certificate and appendix having complied with the requirements of the standard(s) detailed below:

#### Product

**Defender SR2**  
**Rolux SR3-SOL**  
security shutter

#### Standard

**LPS 1175: Issue 7**  
Requirements and testing procedures for the LPCB approval and listing of intruder resistant building components, strongpoints, security enclosures and free-standing barriers

This certificate and appendix is maintained and held in force through regular surveillance activities



Signed for BRE Global Ltd.

Chris Hunt  
Verifier

17 March 2021  
Date of Issue

13 October 2016  
Date of First Issue



This certificate and appendix remains the property of BRE Global Ltd. and is issued subject to terms and conditions (for details visit [www.redbooklive.com/terms](http://www.redbooklive.com/terms)).

To check the validity of this certificate and appendix please visit [www.redbooklive.com/check](http://www.redbooklive.com/check), scan the QR tag or contact us.

BRE Global Ltd, Watford, WD25 9XX  
T: +44 (0)333 321 8811 E: [enquiries@breglobal.com](mailto:enquiries@breglobal.com)

LPCB is a Registered Trademark of the Building Research Establishment Ltd.



## Appendix to Certificate No: 1137a Armourpost Limited

Issue: 03

### Security Shutters

Product Name	Type	Security Rating <sup>1</sup>	LPCB Ref. No.
Defender SR2	Roller shutter with insulated steel lath	2	1137a/02
	Roller shutter with perforated steel lath		
	Roller shutter with solid steel lath		
Rolux SR3-SOL	Roller shutter with reinforced aluminium lath	3	1137a/01

### Configurations, Sizes and Locking Devices<sup>2</sup>

Product Name (Type)	Orientation	Operation	Minimum Clear Opening Height (m)	Maximum Clear Opening Height (m)	Minimum Clear Opening Width (m)	Maximum Clear Opening Width (m)	Locking Devices
Defender SR2 (insulated steel lath)	Internal face fixed	Direct drive	1.5	7.0	2.0	7.0	Pair of sliding locks on the protected face only
		Chain drive					
		Tubular motor					
Defender SR2 (perforated steel lath)	Internal face fixed	Direct drive	1.5	7.0	2.0	7.0	Pair of sliding locks on the protected face or attack face
		Chain drive					
		Tubular motor					
	Reveal fixed	Direct drive	1.5	7.0	2.0	7.0	Pair of sliding locks on the protected face or attack face
		Chain drive					
		Tubular motor					
Defender SR2 (solid steel lath)	Internal face fixed	Direct drive	1.5	7.0	2.0	7.0	Pair of sliding locks on the protected face or attack face
		Chain drive					
		Tubular motor					

This certificate and appendix is maintained and held in force through regular surveillance activities



Signed for BRE Global Ltd.

Chris Hunt  
Verifier

17 March 2021  
Date of Issue

13 October 2016  
Date of First Issue



This certificate and appendix remains the property of BRE Global Ltd. and is issued subject to terms and conditions (for details visit [www.redbooklive.com/terms](http://www.redbooklive.com/terms)).

To check the validity of this certificate and appendix please visit [www.redbooklive.com/check](http://www.redbooklive.com/check), scan the QR tag or contact us.

BRE Global Ltd, Watford, WD25 9XX  
T: +44 (0)333 321 8811 E: [enquiries@breglobal.com](mailto:enquiries@breglobal.com)

LPCB is a Registered Trademark of the Building Research Establishment Ltd.



## Appendix to Certificate No: 1137a Armourpost Limited

Issue: 03

Product Name (Type)	Orientation	Operation	Minimum Clear Opening Height (m)	Maximum Clear Opening Height (m)	Minimum Clear Opening Width (m)	Maximum Clear Opening Width (m)	Locking Devices
Defender SR2 (solid steel lath) <i>continued</i>	Reveal fixed	Direct drive	1.5	7.0	2.0	7.0	Pair of sliding locks on the protected face or attack face
		Chain drive					
		Tubular motor					
Rolux SR3-SOL (reinforced aluminium lath)	Internal face fixed	Tubular motor	1.2	7.0	1.8	6.0	A 24 V fail-secure industrial solenoid locking system operated via a key switch on the protected face only
	Reveal fixed	Tubular motor	1.2	7.0	1.8	6.0	A 24 V fail-secure industrial solenoid locking system operated via a key switch on the protected face only

### Compatible Substrates

Product Name	Compatible Substrates			
	Brickwork/Blockwork	Reinforced Brickwork / Blockwork	Concrete	Steelwork
Defender SR2	✓	✓	✓	✓
Rolux SR3-SOL	✓	✓	✓	✓

#### Notes:

- The security rating is afforded when the roller shutter is closed and all locks engaged and secured in accordance with the operating and maintenance instructions provided with the product.
- Certification does not cover the use of locking devices or operating devices other than those listed above. Utilisation of unlisted locking devices/mechanisms may affect the level of security offered by the roller shutter.
- The approval applies to the shutters when installed strictly in accordance with the instructions contained in the document titled 'Operation and maintenance manual' Revision B (Rolux SR3-SOL) and 'Operation and Maintenance Manual Security Rated Shutters – SR2' (Defender SR2).

This certificate and appendix is maintained and held in force through regular surveillance activities



Signed for BRE Global Ltd.

Chris Hunt  
Verifier

17 March 2021  
Date of Issue

13 October 2016  
Date of First Issue



This certificate and appendix remains the property of BRE Global Ltd. and is issued subject to terms and conditions (for details visit [www.redbooklive.com/terms](http://www.redbooklive.com/terms)).

To check the validity of this certificate and appendix please visit [www.redbooklive.com/check](http://www.redbooklive.com/check), scan the QR tag or contact us.

BRE Global Ltd, Watford, WD25 9XX  
T: +44 (0)333 321 8811 E: [enquiries@breglobal.com](mailto:enquiries@breglobal.com)

LPCB is a Registered Trademark of the Building Research Establishment Ltd.


